

EXTRUSION APPARATUS FOR THREE-DIMENSIONAL MODELING
CROSS-REFERENCE TO RELATED APPLICATION(S)

None.

BACKGROUND OF THE INVENTION

5 This invention relates to the fabrication of three-dimensional objects using extrusion-based layered manufacturing techniques. More particularly, the invention relates to forming three-dimensional objects from multiple types of modeling materials that are extruded in a flowable state and solidify after being deposited onto a base.

10 Three-dimensional models are used for functions including aesthetic judgments, proofing the mathematical CAD model, forming hard tooling, studying interference and space allocation, and testing functionality. Extrusion-based layered manufacturing machines build up three-dimensional models by extruding solidifiable modeling material from a nozzle tip carried by an extrusion head onto
15 a base. "Wetting" of the base by the extruded material serves to separate the modeling material from the tip. Movement of the extrusion head with respect to the base is performed in a predetermined pattern under computer control, in accordance with design data provided from a computer aided design (CAD) system. Examples of extrusion-based apparatus and methods for making three-dimensional
20 objects are described in Valavaara U.S. Patent No. 4,749,347, Crump U.S. Patent No. 5,121,329, Crump U.S. Patent No. 5,340,433, Crump et al. U.S. Patent No. 5,503,785, Danforth, et al. U.S. Patent No. 5,900,207, Batchelder, et al. U.S. Patent No. 5,764,521, Swanson U.S. Patent No. 6,004,124, Stuffle et al. U.S. Patent No. 6,067,480 and Batchelder, et al. U.S. Patent No. 6,085,957, all of which are
25 assigned to Stratasys, Inc., the assignee of the present invention.

 In the Stratasys FDM® three-dimensional modeling machines of the current art, the CAD design of an object is "sliced" into multiple horizontal layers by a software program. The machines then built up the object layer-by-layer by extruding modeling material in fluent strands, termed "roads". Each extruded road

has a thickness equal to the height of a slice. The material being extruded fuses to previously deposited material and solidifies upon a drop in temperature to form a three-dimensional object resembling the CAD model. The modeling material is typically a thermoplastic or wax material. Alternatively, other types of materials, such as metals, which become flowable when heated, which solidify upon a drop in temperature, and which adhere to the previous layer with an adequate bond upon solidification can be employed.

In an extrusion-based modeling system, modeling material is supplied to the extrusion head as a feedstock of either a liquid or a solid material. Where the feedstock of modeling material is in solid form, a liquifier brings the feedstock to a flowable temperature for deposition. One technique is to supply modeling material in the form of a filament strand. Solid material feedstocks may alternatively be in the form of wafers, rods, slugs, or the like. A pressurization means is used to extrude molten modeling material from the extrusion head.

In modeling systems that employ a filament feed, modeling material is loaded into the machine as a flexible filament wound on a supply spool, such as disclosed in U.S. Patent No. 5,121,329. The extrusion head, which includes the liquifier and a dispensing nozzle, receives the filament, melts the filament in the liquifier, and extrudes molten modeling material from the nozzle. Typically, the filament has a small diameter, such as on the order of 0.070 inches. A pair of motor-driven feed rollers on the extrusion head controllably advance the filament strand into the liquifier, which is heated so as to melt the filament. The liquifier is pressurized by the “pumping” of the strand of filament into the liquifier by the feed rollers. The strand of filament itself acts as a piston, creating a “liquifier pump”. The pressurization extrudes the molten modeling material out of an orifice of the nozzle at a volumetric flow rate, where it is deposited onto a base. The volumetric flow rate is a function of the size of the dispensing orifice and the rate of rotation of the feed rollers. By selective control of the feed-roller motor, the rate of advancement of the strand of filament, and thus the volumetric dispensing rate of

the molten modeling material, can be closely controlled. A controller controls movement of the extrusion head in a horizontal x, y plane, controls movement of the base in a vertical z-direction, and controls the rate at which the feed rollers advance filament into the head. By controlling these processing variables in synchrony, the modeling material is deposited in roads at a desired flow rate, layer-by-layer, in areas defined from the CAD model. The dispensed material fuses and solidifies to form a three-dimensional object resembling the CAD model.

In building a model from a modeling material that thermally solidifies upon a drop in temperature, the modeling base is contained within a temperature-controlled build envelope. The build envelope is preferably a chamber which is heated to a temperature higher than the solidification temperature of the modeling material during deposition, and then gradually cooled to relieve stresses from the material. As disclosed in U.S. Patent No. 5,866,058, this approach anneals stresses out of the model while it is being built so that the finished model is stress free and has very little distortion.

In creating three-dimensional objects by depositing layers of solidifiable material, supporting layers or structures are built underneath overhanging portions or in cavities of objects under construction, which are not supported by the modeling material itself. For example, if the object is a model of the interior of a subterranean cave and the cave prototype is constructed from the floor towards the ceiling, then a stalactite will require a temporary support until the ceiling is completed. A support structure may be built utilizing the same deposition techniques and apparatus by which the modeling material is deposited. The apparatus, under appropriate software control, produces additional geometry acting as a support structure for the overhanging or free-space segments of the object being formed. Support material may be dispensed in a like fashion as the modeling material and in coordination with the dispensing of the modeling material, to build up supporting layers or a support structure for the object. Support material is deposited either from a separate dispensing head within the modeling apparatus, or

by the same dispensing head that deposits modeling material. A support material is chosen that will adhere to the modeling material during construction, and that is removable from a completed object. Various combinations of modeling and support materials are known, such as are disclosed in U.S. Patent No. 5,503,785.

5 To accommodate the dispensing of two different materials, the above-mentioned '329 patent discloses a dispensing head having multiple supply passages into which materials of different compositions may be directed, with each passage terminating in a separate dispensing orifice. The dispensing orifices of the '329 patent are arranged on a single broad-based nozzle tip, as shown in Figure 11
10 thereof. Experimentation with broad-faced dispensing has tips taught, however, that a broad-faced tip drags against the road being extruded and smears out object features. Object corners are particularly problematic. If a corner does not get out from under a tip face before the tip changes directions, the tip face will drag against the corner. As the outer diameter of the tip face increases, the corner radius will
15 increase as well, so that a narrow deposited road no longer makes fine features.

To overcome the feature smearing problems of multiple orifices, the above-mentioned '785 patent teaches an extrusion head having independent nozzle tips. The apparatus of the '785 patent uses an electromechanical method to move one tip higher or lower than the other, so that only the tip through which material is being
20 extruded will contact the part surface. While the apparatus of the '785 patent eliminates smearing problems, it introduces significant issues of alignment and calibration. Z-axis calibration of the tips must be verified, as well as X and Y offset calibration. Calibration requirements decrease throughput and reliability. The mechanical complexity of toggling the two tips additionally lowers reliability and
25 increases cost of the machine.

Two other methods for accommodating the dispensing of two different materials are also known: (1) providing two extrusion heads, each including one dispenser for receiving and dispensing one of the modeling materials (such as is disclosed in the '124 patent); and (2) providing a single extrusion head that

dispenses two materials through a single orifice in a common dispensing tip, each material being provided to the tip from a separate flow path in the extrusion head (such as is shown in FIG. 6 of the '329 patent). These methods have disadvantages as well. Where two extrusion heads are provided, cost and size of the modeling machine are increased. Additionally, tip calibration becomes more difficult. A single tip dispensing two different materials avoids calibration issues but introduces other problems. The tip needs to be purged of one material before the other material can be dispensed, in order to avoid mixing of dissimilar materials. Material as well as build time are wasted in purging the tip. Also, if any of a first material remains despite the purging effort, the remaining first material will contaminate the second material resulting in possible degradation of model quality.

None of the known methods for dispensing multiple materials from different material supply sources are entirely satisfactory. There is an unmet need for a dispensing apparatus that dispenses multiple types of modeling materials and is free from the disadvantages of the prior art.

BRIEF SUMMARY OF THE INVENTION

The present invention is a multi-tip extrusion apparatus for three-dimensional modeling and a design methodology, whereby a single extrusion head carrying multiple dispensers having approximately co-planar, fixed-position tips is used to deposit multiple types of materials from distinct material supply sources. The tips are spaced apart a distance great enough so that a road of material extruded by a leading one of the tips will cool and shrink from the plane of the tips so that it is not smeared by contact with a trailing one of the tips. The apparatus of the present invention avoids the smearing, calibration, reliability, cost and throughput issues of the prior art techniques, enabling efficient production of good quality models. Additionally, by thermally insulating the dispensers from one another, the present invention may be utilized to dispense modeling materials having differing operating temperature ranges.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a front elevation of a first exemplary embodiment of an extrusion apparatus according to the present invention.

Figure 2 is a left side elevation of an extrusion head which incorporates the
5 extrusion apparatus of Figure 1, with a portion shown in sectional.

Figure 3 is a sectional view of a portion of the first exemplary embodiment of an extrusion apparatus, taken along a line 3-3 of Figure 2.

Figure 4 is an enlarged sectional view of the two tips of the extrusion apparatus of Figure 3, shown in a dispensing mode.

10 Figure 5 is a bottom plan view of a second exemplary embodiment of an extrusion apparatus according to the present invention.

Figure 6 is a front elevation of a third exemplary embodiment of an extrusion apparatus according to the present invention.

15 Figure 7 is a cross-sectional view of the nozzle of the extrusion apparatus of Figure 6.

DETAILED DESCRIPTION

The multi-tip extrusion apparatus and design methodology of the present invention may be employed with respect to various types of modeling or prototyping systems which form three-dimensional objects by extruding solidifiable
20 modeling material onto a base. Particularly applicable are those systems which utilize an extrusion head to deposit "roads" of material heated to be flowable, and which material shrinks and solidifies upon a drop in temperature to form a solid model. A preferred material deposition and build-up process is of the type disclosed in U.S. Patent No. 5,121,329.

25 Figure 1 shows an extrusion apparatus 10 according to the present invention, comprised of a pair of dispensers 12 and 14 carried by a body 16. Each of the dispensers 12 and 14 is adapted to receive and dispense material from a distinct material supply source, such as is illustrated in Figure 2. In a typical modeling application, one of dispensers 12 and 14 will receive and dispense a

modeling material, while the other will receive and dispense a support material. Alternatively, the materials may be modeling materials of different colors or having other diverse properties.

Figure 2 shows an extrusion head 18 comprised of the extrusion apparatus
5 10 mounted to a carriage 20. The extrusion head 18 is electrically coupled to a system controller 21. As shown, the carriage 20 is movable in a horizontal plane along X and Y axes under control of the controller 21, to permit depositing the material in a known manner in successive layers onto a horizontal base movable along a vertical Z-axis (not shown). Alternatively, it is recognized in the art that
10 any three-dimensional relative movement between the extrusion head 18 and the base may be implemented to form a three-dimensional object. In the embodiment shown, carriage 20 includes a conduit 22 which receives a strand of filament 24 from a supply spool (not shown) of a type known in the art. The filament 24 is formed of a solid material that is flowable when heated and that is to be used in
15 forming a model or a support structure for the model. Carriage 20 additionally includes a pair of feed rollers 26 and 28, a motor 30 and a gear 32, which comprise a suitable filament feed mechanism of a type known in the art. The roller pair 26 and 28 controllably advance the filament strand 24 into the dispenser 12. As shown, roller 26 is a drive roller while roller 28 is an idler. Motor 30 drives the
20 roller 26 via the gear 32. A second filament feed mechanism (not shown) is provided on carriage 24, supplying a filament strand to dispenser 14 from a different supply spool (not shown).

As shown in Figures 1 - 3, the pair of dispensers 12 and 14 are comprised of a pair of flow tubes 34, a nozzle 36 defining two separate flow channels 38, and
25 a pair of co-planar discharge tips 40 of the nozzle 36. Each of the dispensers 12 and 14 define a separate and distinct flow path through the body 16. Each flow tube 34 has a receiving end 42 which defines an inlet to the flow path and a dispensing end 44 positioned to deliver a flow of material to one of the flow channels 38 of the nozzle 36. In the embodiment shown, the flow tubes 34 are thin-wall tubes of the

type disclosed in U.S. Patent No. 6,004,124. The flow tubes 34 are secured to the nozzle 36 such as by brazing. The flow tubes 23, the nozzle 36 and the body 16 are made of a heat conductive material, so as to enable maintaining the flow path at a temperature at which the material being supplied is flowable. The body 16 contains a heating rod 46 extending therethrough. Heating rod 46 is ohmically controlled by the system controller 21 to heat the body 16, which conducts heat to the flow tubes 34 and the nozzle 36. Where the material is supplied as a solid, as in the embodiment shown, the material is liquified in the flow tubes 34, and then flows through the nozzle 36 for dispensing. To monitor the temperature of the extrusion apparatus 10, a thermocouple may be utilized. A thermocouple 48 is shown positioned in the nozzle 36 between the flow channels 38, allowing careful monitoring of the discharge temperature of the material by the system controller 21. If the temperature gets too high, the system controller 21 can toggle off the heating rod 46.

The body 16 may be conveniently manufactured in multiple sections which are mechanically detachable to permit cleaning and replacement of the dispensers 12 and 14. As illustrated in Figure 2, the body 16 has a back section 47 and a front section 49. The dispensers 12 and 14 clamp between the sections 47 and 49, in a manner similar to that described in U.S. Patent No. 6,004,124.

As shown in Figures 3 and 4, each dispensing tip 40 defines a discharge orifice 50 through which molten material is extruded. Each discharge orifice 50 receives flowable material from one of the flow channels 38 of the nozzle 36. Figure 4 illustrates the dispensing of extrudate material onto a base 52 by one of the tips 40, so as to build up a three-dimensional object. The base 52 may be a substrate approximating a plane on which models are built, or it may be previously deposited layers of modeling material. The material is extruded as a road 54 having a thickness h . As shown in Figure 4, the extrusion head 20 carrying extrusion apparatus 10 is moving forward at a velocity v as material is extruded through the orifice 50 of the leading tip 40 and the trailing tip is idle.

In a typical application, the velocity v varies as the extrusion head 20 proceeds through a path comprising a start point, a stop point and multiple vertices. Each vertex is assigned a velocity v , representing the velocity at which the extrusion head 20 can be driven through that vertex without exceeding an allowable error.

5 The extrusion head 20 preferably accelerates and decelerates between vertices so as to achieve a high throughput, in a manner such as is disclosed in U.S. Patent No. 6,054,077.

As mentioned above, the tips 40 of the first exemplary embodiment are co-planar. The tips 40 each have a downward face 56 and the faces 56 are at the same

10 Z-height. In practice of the present invention, typical manufacturing tolerances will result in the tip faces being in only approximately the same plane (i.e., approximately the same Z-height). Approximate co-planarity is acceptable within the tolerances given below. In reference to Fig. 4, each downward face 56 has an outer diameter d_o and an inner diameter d_i defining the orifice 50. The inner and

15 outer diameter of the tips 40 may be the same, or these dimensions may be different, as desired for a given application. The centerline tip-to-tip spacing is given by the variable s_c , while the spacing between the tip faces 56 is given by the variable s . According to the design methodology of the present invention, a minimum spacing between the tips 40 is mathematically predicted according to the

20 tip geometry, build conditions and extrudate material of a given application, so that one tip will not smear the extrudate deposited by the other. The tip spacing requirements will now be described.

The material deposited is one which will solidify upon encountering a predetermined condition, such as the controlled temperature in a build envelope in

25 which modeling takes place. Virtually all materials of interest shrink as they cool and solidify. According to the present invention, the spacing s between the tip faces 54 is greater than or equal to a predetermined minimum value which provides a predetermined time-lag Δt between the two tip faces 56. The spacing between the tips 40 is made great enough to allow extrudate material freshly deposited by the

leading tip 40 to cool and shrink before the trailing tip 40 passes over it, so that the trailing tip 40 will not drag across and smear a road 54 that it did not extrude. This design overcomes the problem of the prior art broad-faced tips, wherein feature detail would be destroyed by the passing of a non-extruding tip surface. The minimum tip spacing can be calculated for a given tip geometry, build conditions and extrudate material. Before describing the mathematical analysis, the following additional parameters are first defined:

	v_{\min}	=	minimum tip velocity at a vertex
	a_{\max}	=	maximum tip acceleration
10	k_e	=	extrudate thermal conductivity
	C_p	=	extrudate heat capacity
	T_e	=	extrudate temperature emerging from tip
	T_g	=	extrudate temperature upon relative solidification
	T_b	=	build environment temperature
15	$T(t)$	=	extrudate temperature t seconds following its emergence from the tip
	α	=	extrudate thermal expansion coefficient
	ρ	=	extrudate average density
	k_a	=	air thermal conductivity
20	K_e	=	extrudate thermal diffusivity

The thermal diffusivity K_e is defined according to the equation:

$$K_e = \frac{k_e}{C_p \rho} \quad (1)$$

As the road 54 deposited by the leading tip 40 cools, it shrinks away from the z-plane of the tips. In order to prevent the trailing tip 40 from dragging across and smearing the road 54, the spacing s between the tip faces 56 is made great enough so that the road 54 should shrink sufficiently during the transit time between the two tips 40 as to leave a gap between the road 54 and the trailing tip face 56. According to the present invention, the spacing s is a distance calculated to result in at least a critical gap g_c between the trailing tip face 56 and the extruded

road 54. We define the critical gap g_c as the amount of air between the trailing tip face 56 and the extruded road 54 that doubles the thermal resistance between the trailing tip face 56 and the center of the road (as compared to no gap). Using this definition, and assuming perfect co-planarity of tip faces 56, the critical gap may be expressed according to the equation:

$$g_c = \frac{h}{2} \left(\frac{k_a}{k_e - k_a} \right) \quad (2)$$

Additionally, the fractional expansion of the road thickness (i.e. g_c/h) is known to be equal to the product of the extrudate thermal expansion coefficient and the drop in extrudate temperature from the time it is deposited to the time the trailing tip 40 goes by. The drop in extrudate temperature required to create the critical gap may thus be characterized by the following equation:

$$T_e - T(t) = \frac{g_c}{h\alpha} \quad (3)$$

The time required to create this change in temperature (ignoring air convection) can be calculated according to the equation¹:

$$\Delta t = \frac{0.3h^2}{K_e} \quad (4)$$

Assuming that a corner is printed at the minimum tip vertex velocity, the criteria for the spacing between the tips becomes:

$$v_{\min} \Delta t + \frac{1}{2} a_{\max} \Delta t^2 \leq s \quad (5)$$

Several observations can be made regarding tip spacing criteria in a three-dimensional fused deposition modeling system:

- Spacing requirements increase linearly with minimum tip

¹ H.S. Carslaw and J.C. Jaeger, Conduction of Heat in Solids, Oxford Science Publications, 2d ed., p. 98.

vertex velocity.

- Spacing requirements increase linearly with maximum tip acceleration.
- Spacing requirements increase quadratically with road thickness for low acceleration gantries. Stated otherwise, decreasing the road thickness offsets the effects of increasing velocity.
- Spacing requirements increase as the fourth power of road thickness for high acceleration gantries ($a_{\max} > 2v_{\min}/\Delta t$).
- Spacing requirements decrease with increasing extrudate thermal conductivity.
- Spacing requirements decrease as the temperature of the emerging extrudate is increased, for a fixed build environment temperature (more thermal shrink and faster temperature change).
- Spacing requirements increase linearly with tip outer diameter (since $s = s_c - d_o$ for same-sized tips).
- An acceptable manufacturing tolerance on the tip face coplanarity is that the z-height of the tip faces (measured along the center line of the orifices) may be offset a distance approaching the critical gap g_c . Within this tolerance range, the trailing tip should have at least about a clearance fit with the extruded road.
- It is desirable to keep the tips as close together as the criteria permit, as this will minimize impact of any nominal tilt of the base from horizontal.

For some applications, it may be desirable to deposit more than two different types of materials from the same extrusion head. For such applications,

the present invention can be utilized in an embodiment having more than two tips, such as is illustrated in Figure 5. Figure 5 shows a nozzle 60 having three tips 40. As with the first exemplary embodiment described above, the tips 40 of nozzle 60 are integral with dispensers adapted to receive material from three different material supply sources, permitting the selective dispensing of any one of the three materials. The tip spacing criteria derived with respect to the first exemplary embodiment having two tips 40 applies also to embodiments having three or more tips. Applying the spacing criteria to an embodiment having three or more tips, the minimum spacing between any two of the tips must satisfy equation 5.

EXAMPLE

An example is given in which theoretical results are compared to experimental results. In this example, the build conditions are that of a Stratasys FDM® three-dimensional modeling machine depositing ABS thermoplastic, according to the parameters given in Table 1 below:

TABLE 1

VARIABLE	VALUE
d_o	45 mils (1.14E-4 meter)
d_i	12 mils (3.05E-4 meter)
s_c	100 mils (2.54E-3 meter)
h	10 mils (2.54E-4 meter)
v_{\min}	0.9 ips (0.023 meter/sec)
a_{\max}	3 inches/sec ² (7.77E-3 g's)
k_e	1.4 watt/(meter °C)
C_p	1.8 joule/(gram °C)
T_e	270 °C
T_g	140 °C
T_b	70 °C
α	8E-5/ °C
ρ	1.1 gram/centimeter ³
k_a	0.016 watt/(meter °C)

The thermal diffusivity for the above example parameters, calculated according to equation (1), is $7.07\text{E-}7$ meters²/sec. The critical gap, calculated according to equation (2), is 0.06 mils (1.5 microns). Applying equation (3), the change in temperature required to create the critical gap is predicted to be 72 °C. The time required to create this change in temperature, predicted according to equation (4), is 27 milliseconds. Finally, equation (5) predicts that the spacing s between the tip faces should be greater than or equal to 0.025 inches. A nozzle having a spacing s of 0.065 inches was utilized on a Stratasys FDM three-dimensional modeling machine depositing ABS thermoplastic under the above example parameters. The model quality was observed to be unimpaired by the passing of the trailing tip.

A third exemplary embodiment of the present invention is shown in Figures 6 and 7. Figure 6 shows an extrusion apparatus 70 having two dispensers 72 and 74 in a body 76, wherein the body 76 further includes a thermal insulator 78 and two heating rods 46. The thermal insulator 78 is positioned between the dispensers 72 and 74 to provide a degree of thermal separation between the dispensers. The two heating rods 46 are located on opposite sides of the thermal insulator 78. The dispensers 72 and 74 are of the same general type as dispensers 12 and 14 of embodiment one. The dispensers 72 and 74 share a common nozzle 82 which includes two dispensing tips 84. As is best shown in Figure 7, the thermal insulator 78 is ambient air that fills a vertical channel 80 extending through the body 76 and the nozzle 82, and a horizontal channel 86 extending through the nozzle 82. The air insulator may be stagnant air or moving air. The thermal insulator 78 may alternatively be any insulating material that will provide a desired degree of thermal separation between the two dispensers. The thermal insulator 78 allows the dispensers 72 and 74 to be maintained at diverse temperatures by the heating rods 46. Two thermocouples 48 are thus utilized, one positioned in each of the dispensers 72 and 74. The thermal separation between the dispensers 72 and 74 provided by the third exemplary embodiment is useful where it is desirable to maintain the two extrusion materials at different temperature elevations, such as

where the two materials have significantly different melting points. Again, the tip spacing criteria derived with respect to the first exemplary embodiment applies equally to the third exemplary embodiment.

Various modification may be made to the thermally-insulated embodiment shown in Figures 6 and 7 that will increase the temperature gradient between the two dispensers 72 and 74. For example, increasing the size of the channel 80 will provide a greater degree of thermal separation between dispensers 72 and 74 by increasing the volume of insulating air, as will boring channels through the body 76 to the exterior walls of the channel 80. It should further be understood that the body 76 and nozzle 82 can be physically separated into right and left sections by a solid insulator (*e.g.*, a high temperature plastic or a ceramic material), to maximize the temperature gradient between the dispensers 72 and 74. It should be noted, however, that providing the nozzle as a single piece is advantageous provided that adequate thermal separation can be maintained, as calibration of tip position becomes an issue using a multi-piece nozzle. The thermally-insulated embodiment can be further modified to include three or more dispensers, with some or all of the dispensers thermally separated from one another, with each of the dispenser tips satisfying the spacing criteria.

Although the present invention has been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without departing from the spirit and scope of the invention. For example, it should be understood that while the present invention is shown and described herein as receiving modeling material in the form of a filament strand provided by a filament feed mechanism, the extrusion apparatus of the present invention can be utilized to advantage in modeling systems which receive other types of material feed stocks from other types of feed mechanisms, including liquid feed stocks. It will also be appreciated that various modifications may be made to the dispensers in keeping with the teachings of the present

invention. The flow tubes, for example, could be eliminated by instead boring flow channels through the body itself. It will further be appreciated that innumerable other various modifications may be made to the extrusion apparatus of the present invention.

100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000